



Quick guide ReSound LiNX Quattro™ 61

GN Making Life Sound Better

My hearing aid information	Progr (if set up
Product: ReSound LiNX Quattro	PROG
Model: 61	1
Serial number (R):	2
Serial number (L):	3

Battery size: Lithium-ion

ams:


p by your hearing care professional)

PROGRAM	WHEN TO USE	BEEPS
1		1
2		2
3		3
4		4

Get to know your hearing aid

- 1. Push button
- 2. Receiver
- 3. Open dome
- 4. Receiver wire


- 5. LED light indicator
- 6. Microphones
- 7. Right/Left indicator
- 8. Serial number and model



View ReSound's hearing aid tutorial videos at youtube.com/resoundus.

6.2 Hearing aid charger


- 1. Hearing aid charging bay
- 2. Receiver bay
- 3. Hearing aid battery indicator
- 4. Left indicator (blue)
- 5. Right indicator (red)
- 6. Charger battery indicator
- 7. Charging cable
- 8. Charging cable port (micro-USB)



What you need to know

Getting started: On/Off function

Your hearing aids are automatically turned on when they are removed from the hearing aid charger. They can also be turned on and off manually by pressing the push button for 5 seconds.



How to charge your hearing aids

 Plug the power adaptor into a power outlet and connect the charging cable to the hearing aid charger.



- Place both hearing aids in the charging bays. The right side is marked with a red dot and the left side is marked by a blue dot.
- Place hearing aids so the receivers go into the receiver bay.
- The LED on the hearing aids slowly pulsates when charging and will stay solid when fully charged.







When fully charged On-until removed

 The five LEDs at the front of the charger indicate the battery status of the hearing aid with the lowest battery level for 10 seconds when inserted or removed (while the hearing aids continue to charge).

Hearing Aid Battery Indicators

ricaring Ala Battery maleators		
LEDs	Battery Level	
	0-20%	
0 0	20-40%	
000	40-60%	
0000	60-80%	
00000	80-100%	



For more information

Refer to the user guide included in your hearing aid box.

Your hearing care professional car
be reached at:

View ReSound hearing aid tutorial videos at youtube.com/resoundus.

Manufacturer according to FDA:

GN ReSound North America

8001 E Bloomington Freeway Bloomington, MN 55420 USA

1.888.735.4327 resound.com

ReSound Government Services

8001 E Bloomington Freeway Bloomington, MN 55420 USA 1.800.392.9932

www.resound.com/veterans



How to charge the charger

 Plug the power adaptor into a power outlet and connect the charging cable to the hearing aid charger.



- The three LEDs at the back of the charger show the battery level of the hearing aid charger.
- When the hearing aid charger is fully charged, it has a capacity of at least 3 full hearing aid charges before it needs to be plugged in and recharged.

LEDs	Battery Level
	LED is blinking red. Less than 10% power reserve.
0	10-33% charged
00	33-66% charged
000	66-100% charged

Regular care & maintenance

Daily: Clean your hearing aid.

Keep your hearing aids dry. Clean the hearing aids using a soft cloth or tissue.



Weekly: Clean the receiver tubes and domes (E).

Use a soft cloth to clean the receiver tube and dome on the outside. Do not use water when you are cleaning the receiver tubes.

Flight mode:

Some airlines prohibit the use of wireless hearing aids (RF transmitters) onboard.

To use Flight mode, make sure this is activated by your hearing care professional.

Follow these steps to turn on Flight mode:

- 1. Turn the hearing aid off.
- 2. Press the push button for 9 seconds.
- 3. The hearing aid responds with four times double flashes and double-dings for ten seconds.

To deactivate Flight mode:

1. Turn the hearing aids off and then on.

Regular care & maintenance

As needed: Change dome (E)

ReSound standard domes

- Push the new dome over the receiver.
- 2. Make sure that the new dome is properly and securely maintained.



ReSound tulip domes

Tulip domes consist of two "petals". It is important that the largest petal is the outermost petal. To ensure this:

- Push the largest petal away from the receiver tube using a finger. This bends the petal forward.
- 2. Then push the largest petal back, and it will be placed on top of the smaller petal.








Monthly: Change the wax guard or see your hearing care professional.

For changing $CeruSTOP^{TM}$ (white) wax guards, complete the following steps:

Removal: Insert the removal side of the wax guard tool into the used wax guard so that the shaft of the



Insertion: To insert the new wax guard, gently press the replacement side of the wax guard tool straight into the hole of the sound outlet until the outer ring lies flush with the outside of the receiver. Pull the tool straight out. The new wax guard will remain in place.

Beep/tone indicators

INDICATION

Hearing aid is starting up

Hearing aid is in flight mode

Hearing aid is in streaming

Low battery

mode

BEEP/TONE

Ding (5 or 10)

ding-ding, etc.

Ding-ding,

Ripple tone

Ding, ding, ding, dong

	button to exit streaming mode
View ReSound hearing aid tutorial videos at youtube.com/i	resoundus
If there are any other problems not mentioned in this qu	

ACTION REQUIRED

After dings cease, hearing aid

Use in flight mode if desired,

or turn the hearing aids off

accessory or press the push

Charge battery

is turned on

and then on

Use with wireless

If there are any other problems not mentioned in this guide, please contact ReSound or your hearing care professional.

Troubleshooting

SYMPTOM	CAUSE	POSSIBLE REMEDY
No sound	Blocked earmold or tube	Clean earmold or tube
	Blocked wax guard	Replace wax guard (D) or consult your hearing care professional
Not loud enough	Blocked earmold or dome (E)	Clean earmold, replace dome (E), replace guard (D)
	Change in hearing, volume too low	Consult your hearing care professional
	Excessive ear wax	Consult your hearing care professional
Excessive	Incorrect earmold placement	Re-insert earmold carefully
whistling/feedback	Incorrect dome (E) placement	Re-insert dome (E)
	Excessive ear wax	Clean guard/consult your hearing care professional
	If none of the above	Consult your hearing care professional
Wireless does not work	Device may be in flight mode	Turn the hearing aid off and then back on
Hearing aid is not	Does the hearing aid sit correctly in the charger? Is the hearing aid charger charged?	Reinsert the hearing aid in the charger.
charging		Plug the charger into a power outlet and connect the charger cable to the hearing aid charger.
Why do my hearing aids not turn on automatical- ly, although they have been in the charger for an extended period of time?	If you leave your hearing aids in the charger for more than 24 hours, the charger will go into standby mode and turn off the power of the hearing aids. If the charger runs out of battery power during charging of the hearing aids, it will instruct the hearing aids to turn off power to preserve energy.	Remove the hearing aids from the charger and press the push button for 5 seconds to turn the hearing aids on manually.